

## Kaiflex EF kevalai

Izoliacijos storis, mm	vidinis skersmuo, mm	Kodas	Tiekimo kategorija	pak. tūris m <sup>3</sup> /pak.	Kiekis		
					m/pak	pak/paletė	m/paletė
9	12	63700	C	0.290	264.0	24	6336
	15	63303	C	0.290	240.0	24	5760
	18	63702	C	0.290	192.0	24	4608
	22	63305	C	0.290	156.0	24	3744
	28	63306	C	0.290	124.0	24	2976
	35	63307	C	0.290	92.0	24	2208
	42	63308	C	0.290	70.0	24	1680
	48	63383	C	0.270	60.0	24	1440
	54	63384	C	0.270	60.0	24	1440
	60	63391	C	0.270	60.0	24	1440
	64	63395	C	0.270	54.0	24	1296
76	63396	C	0.270	54.0	24	1296	
13	12	63311	B	0.290	172.0	24	4128
	15	63703	B	0.290	144.0	24	3456
	18	63704	B	0.290	128.0	24	3072
	22	63705	B	0.290	108.0	24	2592
	28	63706	B	0.290	84.0	24	2016
	35	63316	B	0.290	76.0	24	1824
	42	63317	B	0.290	56.0	24	1344
	48	63318	C	0.290	48.0	24	1152
	54	63319	B	0.290	46.0	24	1104
	60	63320	B	0.290	40.0	24	960
	64	63321	C	0.290	40.0	24	960
76	63322	B	0.290	34.0	24	816	
89	63323	B	0.290	30.0	24	720	
19	15	63708	C	0.290	80.0	24	1920
	18	63709	C	0.290	80.0	24	1920
	22	63710	C	0.290	72.0	24	1728
	28	63711	C	0.290	56.0	24	1344
	35	63335	B	0.290	48.0	24	1152
	42	63336	B	0.290	40.0	24	960
	48	63712	B	0.290	36.0	24	864
	54	63338	B	0.290	30.0	24	720
	60	63339	B	0.290	28.0	24	672
	64	63340	C	0.290	28.0	24	672
76	63341	B	0.290	28.0	24	672	
89	63342	B	0.290	22.0	24	528	
25	18	63713	C	0.290	48.0	24	1152
	18	63713	C	0.290	48.0	24	1152
	22	63350	C	0.290	42.0	24	1008
	28	63351	C	0.290	40.0	24	960
	35	63352	C	0.290	32.0	24	768
	42	63353	C	0.290	24.0	24	576
	48	63354	C	0.290	24.0	24	576
	54	63355	C	0.290	22.0	24	528
	60	63356	C	0.290	22.0	24	528
	64	63357	C	0.290	18.0	24	432
76	63358	C	0.290	18.0	24	432	
89	63359	C	0.290	14.0	24	336	

Pagal užsakymus tiekiami ir kitų skersmenų, storių kevalai.

Tiekimo kategorija:

- A sandėliuojamas gaminy
- B pristatymo terminai derinami (apytiksliai 15-20d).
- C pristatymo terminai derinami atskiru susitarimu. Yra minimalus užsakymo kiekis.